

ALUMINUM HAZARDOUS LOCATION CLASS 1 DIV 2 Fixture

IR3-4-2-26-UNV-T8

IR3-4-2-46-UNV-T5HO

4-FT., 2-LAMP, T8 (32-watt), FLUORESCENT HAZARDOUS LOCATION FIXTURE

4-FT., 2-LAMP, T5HO (54 watt), FLUORESCENT HAZARDOUS LOCATION FIXTURE



FIXTURE FEATURES

Intended Use

Intended for hazardous location applications:

- Class I, Div. 2-Groups A, B, C, D

Typical applications include solvent and cleaning areas, petrochemical facilities, marine facilities, waste treatment plants and food processing applications.

Construction

- Extruded aluminum housing and clear lens.
- End mounting brackets are standard with fixture.

Ballast

Energy efficient, 120-277 multi-volt, electronic, automatic resetting, program start (T5HO) and instant start (T8) ballasts are standard in all fixtures.

Listings

UL 595 – Outdoor Marine Type (salt water)

UL 844 – Class I, Div 2, A,B,C,D

Meets Coast Guard Specifications

Approximate Fixture Dimensions & Weights

Length: 49.75-inches

Width: 6.5-inches

Height (to top of fixture) 6.5-inches

Height (to top of mounting brackets) 11.5-inches

Weight: 33 lbs

Mounting

Fixture can be surface mounted or suspended.

Warranty

Fixture is warranted for five years from delivery date against manufacturing defects. Ballast warranty is provided through the ballast manufacturer.

Accessories

- Wire Guard
- Safety Cable
- Shock Mount

ALUMINUM HAZARDOUS LOCATION CLASS 1 DIV 2 Fixture
IR3-4-2-26-UNV-T8
IR3-4-2-46-UNV-T5HO

4-FT., 2-LAMP, T8 (32-watt), FLUORESCENT HAZARDOUS LOCATION FIXTURE
4-FT., 2-LAMP, T5HO (54 watt), FLUORESCENT HAZARDOUS LOCATION FIXTURE



DIMENSIONS

- A- 49 ³/₄ "
- B- 47 "
- C- 4 ³/₄ "
- D- 7 "
- E- 6.5 "
- F- 6.5 "

